

Motor-Driven Metering Pump alpha

The cost-effective solution for simple applications in the lower performance range.



The motor-driven metering pump alpha is the metering pump for liquid media and the optimum solution for simple applications. Robust, low-noise, chemical-resistant, with precise metering and good suction capacity.

Technical Details

- Stroke length adjustment by changing the eccentricity on the pump drive when the pump is idle
- Stroke length adjustment in 10% steps
- Diaphragm deflection from the centre position
- Soft controlled suction and compression strokes



Motor-Driven Metering Pump alpha

The cost-effective solution for simple applications in the lower performance range.

Technical Data

Pump type	Pump capacity at max. back pressure			Delivery rate at medium back pressure			Stroke rate Strokes/min	Stroke length mm	Connector size Ø x i Ø mm	Suction lift m WC	Shipping weight kg
	bar	l/h	ml/stroke	bar	l/h	ml/stroke					
50 Hz											
ALPc 1001	10	1.0	0.29	5	1.1	0.32	30	2	6 x 4	5.1	3.0
ALPc 0230	2	30.6	3.98	1	32.7	4.26	128	3	12 x 9	3.1	3.0
ALPc 0417	4	17.0	2.51	2	18.3	2.76	128	3	8 x 5	4.1	3.0
ALPc 0707	7	6.9	1.98	3	7.7	2.21	58	3	8 x 5	4.1	3.0
ALPc 1002	10	1.8	0.52	5	2.1	0.60	58	2	6 x 4	5.1	3.0
ALPc 1004	10	3.5	1.01	5	3.9	1.12	58	3	8 x 5	5.1	3.0
ALPc 1008	10	7.7	1.00	5	8.6	1.12	128	3	8 x 5	5.1	3.0
60 Hz											
ALPc 0230	2	34.4	3.72	1	39.2	4.24	154	3	12 x 9	3.1	3.0
ALPc 0417	4	20.6	2.45	2	21.9	2.75	154	3	8 x 5	4.1	3.0
ALPc 0707	7	8.3	2.00	3	9.2	2.22	69	3	8 x 5	4.1	3.0
ALPc 1001	10	1.2	0.29	5	1.3	0.31	36	2	6 x 4	5.1	3.0
ALPc 1002	10	2.2	0.53	5	2.6	0.63	69	2	6 x 4	5.1	3.0
ALPc 1004	10	4.1	0.99	5	4.7	1.14	69	3	8 x 5	5.1	3.0
ALPc 1008	10	8.9	0.96	5	10.4	1.13	154	3	8 x 5	5.1	3.0

All data calculated with water at 20 °C.

Materials in Contact with the Medium

Identity code of material	Dosing head	Connection on suction/ discharge side	Ball seat	Seals	Balls
PPE	Polypropylene	Polypropylene	EPDM	EPDM	Ceramic
PPB	Polypropylene	Polypropylene	FKM A	FKM A	Ceramic
NPE	Clear acrylic	PVC	EPDM	EPDM	Ceramic
NPB	Clear acrylic	PVC	FKM A	FKM A	Ceramic
PVT	PVDF	PVDF	PVDF	PTFE	Ceramic

Metering diaphragm with PTFE coating for all designs

FKM = fluorine rubber

Motor Data

Type	Split pole motor with integrated thermal overload protection
Electrical connection	220 – 240 V, 50/60 Hz (variant A)
Output	50 W (at 230 V/50 Hz)
Power consumption	0.4 A (at 230 V/50 Hz)

Warranty: The warranties listed in the General Terms and Conditions of Sale apply; there is a warranty period of 12 months for the alpha pump drive.